

Schneckengewindeschelle Typ L / 9 mm | W5



Technische Merkmale in der Übersicht

Norm: DIN 3017

Material: Edelstahl | DIN 1.4401 AISI-316

Schraubenmaterial: Edelstahl (AISI-316) Cu

| Spannbereich mm | Bandbreite mm | Drehmoment Nm | Betriebsdruck bar | Artikel-Nr. |
|--------------------|------------------|------------------|----------------------|-----------------|
| 8 – 16 | 9,0 | 3,0 | 45 | 30000-W5-09-016 |
| 12 – 22 | 9,0 | 3,0 | 45 | 30000-W5-09-022 |
| 16 – 27 | 9,0 | 3,5 | 42 | 30000-W5-09-027 |
| 20 – 32 | 9,0 | 3,5 | 36 | 30000-W5-09-032 |
| 20 – 35 | 9,0 | 4,0 | 34 | 30000-W5-09-035 |
| 25 – 40 | 9,0 | 4,0 | 32 | 30000-W5-09-040 |
| 30 – 45 | 9,0 | 4,0 | 28 | 30000-W5-09-045 |
| 32 – 50 | 9,0 | 4,0 | 24 | 30000-W5-09-050 |
| 40 – 60 | 9,0 | 4,0 | 19 | 30000-W5-09-060 |
| 50 – 70 | 9,0 | 4,0 | 17 | 30000-W5-09-070 |
| 60 – 80 | 9,0 | 4,0 | 15 | 30000-W5-09-080 |
| 70 – 90 | 9,0 | 4,0 | 13 | 30000-W5-09-090 |
| 80 – 100 | 9,0 | 4,0 | 11 | 30000-W5-09-100 |
| 90 – 110 | 9,0 | 4,0 | 10 | 30000-W5-09-110 |
| 100 – 120 | 9,0 | 4,0 | 9 | 30000-W5-09-120 |
| 110 – 130 | 9,0 | 4,0 | 8 | 30000-W5-09-130 |
| 120 – 140 | 9,0 | 4,0 | 7 | 30000-W5-09-140 |
| 130 – 150 | 9,0 | 4,0 | 6 | 30000-W5-09-150 |
| 140 – 160 | 9,0 | 4,0 | 5 | 30000-W5-09-160 |

Auch in W1, W2 und W4 lieferbar!