

Schneckengewindeschelle Typ S / 12 mm | W1



Technische Merkmale in der Übersicht

Norm: DIN 3017

Material: Stahl S | EN 10292 | DIN 1.0935

Schraubenmaterial: Stahl QST 36-3 verzinkt Cr3 | DIN 1.0213

Spannbereich mm	Bandbreite mm	Drehmoment Nm	Betriebsdruck bar	Artikel-Nr.
16 – 27	12	4,2	45	30001-W1-12-027
20 – 32	12	5,2	45	30001-W1-12-032
25 – 40	12	5,2	40	30001-W1-12-040
30 – 45	12	5,2	35	30001-W1-12-045
32 – 50	12	6,0	35	30001-W1-12-050
40 – 60	12	6,8	30	30001-W1-12-060
50 – 70	12	6,8	25	30001-W1-12-070
60 – 80	12	6,8	20	30001-W1-12-080
70 – 90	12	6,8	17	30001-W1-12-090
80 – 100	12	6,8	14	30001-W1-12-100
90 – 110	12	6,8	12	30001-W1-12-110
100 – 120	12	6,8	10	30001-W1-12-120
110 – 130	12	6,8	8	30001-W1-12-130
120 – 140	12	6,8	7	30001-W1-12-140
130 – 150	12	6,8	6	30001-W1-12-150
140 – 160	12	6,8	5	30001-W1-12-160
150 – 170	12	6,8	4	30001-W1-12-170
160 – 180	12	6,8	3	30001-W1-12-180
170 – 190	12	6,8	2	30001-W1-12-190
180 – 200	12	6,8	2	30001-W1-12-200
190 – 210	12	6,8	1,8	30001-W1-12-210
200 – 220	12	6,8	1,8	30001-W1-12-220
210 – 230	12	6,8	1,6	30001-W1-12-230
220 – 240	12	6,8	1,6	30001-W1-12-240

Auch in W2, W4 und W5 lieferbar!